



On-Track Plant Engineering Conformance Certificate

This certificate is issued in accordance with RIS-1530-PLT Issue 6

NAME OF VEHICLE ACCEPTANCE BODY

ACCREDITATION CODE

SNC-Lavalin Rail & Transit Verification Limited

21

Vehicle Class / Description

020/Rail-Ability/RT23TFA/0A

Vehicle Owner

A P Webb Plant Hire Ltd

Issue Date

6 July, 2018

Expiry Date

6 July, 2025

Vehicle Number(s)

99709_020120-0


First Of Class

99709 020109-3 on Engineering Conformance Certificate 21/0906/17 against RIS-1530-PLT Issue 6.

Authorised by:

Bryan Lowe

SNC-Lavalin Rail & Transit Verification Limited



OFFICIAL STAMP



SNC-LAVALIN

Reason for issue and Scope of Work

Certification of new Rail-Ability RT23TFA rail trailer.

Serial No. RT23TFA0042. Fleet No. TR74.

Assessed for compliance with RIS-1530-PLT, Issue 6.

Expiry date conforms the requirements of RIS-1530-PLT, Issue 6.

Deviations associated with this certificate

None

Previous Certificate Number

No previous Engineering Conformance Certificate.

Customer Copy

Certificate Number: 21/0398/18



On-Track Plant

Maintenance Plan Details

Rail-Ability 23 Tonne Rail Trailer Maintenance Plan; 23TRTRMPS001; Issue 1; Review C; 30-Sep-2017.

Rail-Ability 20 and 23 Tonne Rail Trailer Operations & Emergency Recovery Procedures; Issue 3 dated Oct-2017.

Limitations of Use

1. It shall only operate inside possessions.
2. In travelling and working modes, the trailer is within Plant gauge, as defined by RIS-1530-PLT.
3. Trailer shall not on/off track or work on live conductor rail lines.
4. Trailer may on/off track, travel and work under live OLE in conjunction with a safe system of work as determined and authorised by taking guidance from the requirements of GE/RT8024.
5. Trailer may not activate train operated points.
6. Trailer shall not travel or work on track with:
 - Cants greater than 200mm; gradients greater than 1:25 and/or curves less than 80m.
7. The trailer cannot be on/off tracked in laden condition.
8. For on/off tracking, a site specific plan shall be used taking account of the requirements of the applicable Module in Network Rail Infrastructure Plant Manual NR/L2/RMVP/0200.
9. In travelling and working mode the trailer shall be the subject to limitations of the towing vehicle.
10. Trailer payload of 20.5 tonnes shall not be exceeded.

Supplementary Information

1. Rail-Ability 4-wheel trailer with 4.5m bed to work with compatible RRV.
2. Serial No. RT23TFA0042; Fleet No. TR74.
3. Fitted with air-release spring-operated emergency/parking brake and air operated service brake.
4. Air parking brake release pressure 9 bar; service brake pressure 0-9 bar.
5. Gross weight: 23 tonnes.
6. Trailer payload: 20.5 tonnes.
7. Tare weight: 2.5 tonnes.
8. Maximum speeds (travel and working) not to exceed:
 - 10mph plain line;
 - 5mph switches and crossings;
 - 5mph working speed;
 - 1mph raised check/guard rails.

Customer Copy

Certificate Number: 21/0398/18